



Differences from HTML4

W3C Working Draft 28 May 2013

This Version:

<http://www.w3.org/TR/2013/WD-html5-diff-20130528/>

Latest Version:

<http://www.w3.org/TR/html5-diff/>

Latest Editor's Draft:

<https://rawgithub.com/whatwg/html-differences/master/Overview.html>

Participate:

[File a bug](#) ([open bugs](#))

Version History:

<https://github.com/whatwg/html-differences/commits>

Previous Versions:

<http://www.w3.org/TR/2012/WD-html5-diff-20121025/>

<http://www.w3.org/TR/2012/WD-html5-diff-20120329/>

<http://www.w3.org/TR/2011/WD-html5-diff-20110525/>

<http://www.w3.org/TR/2011/WD-html5-diff-20110405/>

<http://www.w3.org/TR/2011/WD-html5-diff-20110405/>

<http://www.w3.org/TR/2011/WD-html5-diff-20110113/>

<http://www.w3.org/TR/2010/WD-html5-diff-20101019/>

<http://www.w3.org/TR/2010/WD-html5-diff-20100624/>

<http://www.w3.org/TR/2010/WD-html5-diff-20100304/>

<http://www.w3.org/TR/2009/WD-html5-diff-20090825/>

<http://www.w3.org/TR/2009/WD-html5-diff-20090423/>

<http://www.w3.org/TR/2009/WD-html5-diff-20090212/>

<http://www.w3.org/TR/2008/WD-html5-diff-20080610/>

<http://www.w3.org/TR/2008/WD-html5-diff-20080122/>

Editor:

Simon Pieters ([Opera Software ASA](#)) <simonp@opera.com>

Previous Editor:

[Anne van Kesteren](#) <annevk@annevk.nl>

Copyright © 2013 W3C® ([MIT](#), [ERCIM](#), [Keio](#), [Beihang](#)), All Rights Reserved. W3C [liability](#), [trademark](#) and [document use](#) rules apply.

Abstract

HTML is the core language of the World Wide Web. The W3C publishes HTML5 and

HTML5.1. The WHATWG publishes HTML, which is a rough superset of W3C HTML5.1. "Differences from HTML4" describes the differences of the HTML specifications from those of HTML4, and calls out cases where they differ from each other. This document may not provide accurate information, as the specifications are still actively in development. When in doubt, always check the specifications themselves. [\[HTML5\]](#) [\[HTML5NIGHTLY\]](#) [\[HTML\]](#)

Status of This Document

This section describes the status of this document at the time of its publication. Other documents may supersede this document. A list of current W3C publications and the latest revision of this technical report can be found in the [W3C technical reports index](#) at <http://www.w3.org/TR/>.

This is the 28 May 2013 W3C Working Draft produced by the [HTML Working Group](#), part of the [HTML Activity](#). The Working Group intends to publish this document as a [Working Group Note](#). The appropriate forum for comments is [W3C Bugzilla](#). (public-html-comments@w3.org, a mailing list with a [public archive](#), is no longer used for tracking comments.)

Publication as a Working Draft does not imply endorsement by the W3C Membership. This is a draft document and may be updated, replaced or obsoleted by other documents at any time. It is inappropriate to cite this document as other than work in progress.

This document was produced by a group operating under the [5 February 2004 W3C Patent Policy](#). W3C maintains a [public list of any patent disclosures](#) made in connection with the deliverables of the group; that page also includes instructions for disclosing a patent. An individual who has actual knowledge of a patent which the individual believes contains [Essential Claim\(s\)](#) must disclose the information in accordance with [section 6 of the W3C Patent Policy](#).

Table of Contents

[1 Introduction](#)

[1.1 Scope of This Document](#)

[1.2 History of HTML](#)

[1.3 Open Issues](#)

[1.4 Backward Compatibility](#)

[1.5 Development Model](#)

[2 Syntax](#)

[2.1 Character Encoding](#)

[2.2 The Doctype](#)

[2.3 MathML and SVG](#)

[2.4 Miscellaneous](#)

[3 Language](#)

[3.1 New Elements](#)

[3.2 New Attributes](#)

[3.3 Changed Elements](#)

[3.4 Changed Attributes](#)

[3.5 Obsolete Elements](#)

[3.6 Obsolete Attributes](#)

[4 Content Model](#)

[5 APIs](#)

[5.1 New APIs](#)

[5.2 Changed APIs](#)

[5.3 Extensions to Document](#)

[5.4 Extensions to HTML Element](#)

[5.5 Extensions to Other Interfaces](#)

[5.6 Obsolete APIs](#)

[6 HTML Changelogs](#)

[6.1 Changes from 14 September 2012 to 6 May 2013](#)

[6.2 Changes from 29 March 2012 to 14 September 2012](#)

[6.3 Changes from 25 May 2011 to 29 March 2012](#)

[6.4 Changes from 5 April 2011 to 25 May 2011](#)

[6.5 Changes from 13 January 2011 to 5 April 2011](#)

[6.6 Changes from 19 October 2010 to 13 January 2011](#)

[6.7 Changes from 24 June 2010 to 19 October 2010](#)

[6.8 Changes from 4 March 2010 to 24 June 2010](#)

[6.9 Changes from 25 August 2009 to 4 March 2010](#)

[6.10 Changes from 23 April 2009 to 25 August 2009](#)

[6.11 Changes from 12 February 2009 to 23 April 2009](#)

[6.12 Changes from 10 June 2008 to 12 February 2009](#)

[6.13 Changes from 22 January 2008 to 10 June 2008](#)

[Acknowledgments](#)

[References](#)

1 Introduction

1.1 Scope of This Document

This document covers the W3C HTML5 specification, W3C HTML5.1 specification, and the WHATWG HTML standard. For readability, these are referred to as if they were a single specification: "the HTML specification" or simply "HTML" when something applies equally to all of them; otherwise, they are called out explicitly.

1.2 History of HTML

HTML has been in continuous evolution since it was introduced to the Internet in the early 1990s. Some features were introduced in specifications; others were introduced in software releases. In some respects, implementations and Web developer practices have converged with each other and with specifications and standards, but in other ways, they have diverged.

HTML4 became a W3C Recommendation in 1997. While it continues to serve as a rough guide to many of the core features of HTML, it does not provide enough information to build implementations that interoperate with each other and, more

importantly, with Web content. The same goes for XHTML1, which defines an XML serialization for HTML4, and DOM Level 2 HTML, which defines JavaScript APIs for both HTML and XHTML. HTML replaces these documents. [\[DOM2HTML\]](#) [\[HTML4\]](#) [\[XHTML1\]](#)

The HTML specification reflects an effort, started in 2004, to study contemporary HTML implementations and Web content. The specification:

1. Defines a single language called HTML which can be written in HTML syntax and in XML syntax.
2. Defines detailed processing models to foster interoperable implementations.
3. Improves markup for documents.
4. Introduces markup and APIs for emerging idioms, such as Web applications.

1.3 Open Issues

The contents of HTML, as well as the contents of this document which depend on HTML, are still being discussed on the HTML Working Group and WHATWG mailing lists.

Open issues for WHATWG HTML, see "Issues:" at the top of the specification. The specification also has annotation boxes in the margin which can link to bugs.

Open issues for W3C HTML5 and W3C HTML5.1, see the "Status of This Document" section.

1.4 Backward Compatibility

HTML is defined in a way that is backward compatible with the way user agents handle content. To keep the language relatively simple for Web developers, several older elements and attributes are not included, as outlined in the other sections of this document, such as presentational elements that are better handled using CSS.

User agents, however, will always have to support these older elements and attributes. This is why the HTML specification clearly separates requirements for Web developers (referred to as "authors" in the specification) and user agents; for instance, this means that Web developers cannot use the [isindex](#) or the [plaintext](#) element, but user agents are required to support them in a way that is compatible with how these elements need to behave for compatibility with Web content.

Since HTML has separate conformance requirements for Web developers and user agents there is no longer a need for marking features "deprecated".

1.5 Development Model

The HTML4 specification reached Recommendation status before it was completely implemented in user agents. HTML4 still is not completely implemented, because it

contains various bugs that have been fixed in the current HTML specification, which user agents are much closer to implementing than HTML4.

The WHATWG HTML standard is under continual development where bugs are fixed and new features are introduced over time. Features can also be removed from the specification if they lack implementor interest, are not being used by Web developers, or for other reasons. The WHATWG does not publish frozen snapshots.

The W3C HTML5 specification is trying to reach Recommendation status. New features are generally not added unless they are implemented by at least two browsers and have tests demonstrating interoperability. Minor bug fixes can be applied. This means that W3C HTML5 may contain bugs that have been fixed in WHATWG HTML or W3C HTML5.1, or both.

The W3C HTML5.1 specification is similar to WHATWG HTML: it is under continual development where bugs are fixed and new features are introduced over time, and features can be removed from the specification for the same reasons as with WHATWG HTML. It cherry-picks changes from the WHATWG HTML standard and also gets direct changes. It is expected to eventually go through the same procedure as W3C HTML5, and then a new version will be minted.

2 Syntax

HTML defines a syntax, referred to as "the HTML syntax", that is mostly compatible with HTML4 and XHTML1 documents published on the Web, but is not compatible with the more esoteric SGML features of HTML4, such as [processing instructions](#) and [shorthand markup](#) as these are not supported by most user agents. Documents using the HTML syntax are served with the `text/html` media type.

HTML also defines detailed parsing rules (including "error handling") for this syntax which are largely compatible with HTML4-era implementations. User agents have to use these rules for resources that have the `text/html` media type. Here is an example document that conforms to the HTML syntax:

```
<!doctype html>
<html>
  <head>
    <meta charset="UTF-8">
    <title>Example document</title>
  </head>
  <body>
    <p>Example paragraph</p>
  </body>
</html>
```

The other syntax that can be used for HTML is XML. This syntax is compatible with XHTML1 documents and implementations. Documents using this syntax need to be served with an XML media type (such as `application/xhtml+xml` or `application/xml`) and elements need to be put in the <http://www.w3.org/1999/xhtml> namespace following the rules set forth by the XML specifications. [\[XML\]](#) [\[XMLNS\]](#)

Below is an example document that conforms to the XML syntax of HTML.

```
<?xml version="1.0" encoding="UTF-8"?>
<html xmlns="http://www.w3.org/1999/xhtml">
  <head>
    <title>Example document</title>
  </head>
  <body>
    <p>Example paragraph</p>
  </body>
</html>
```

2.1 Character Encoding

For the HTML syntax, Web developers are required to declare the character encoding. There are three ways to do that:

- At the transport level; for instance, by using the HTTP `Content-Type` header.
- Using a Unicode Byte Order Mark (BOM) character at the start of the file. This character provides a signature for the encoding used.
- Using a `meta` element with a `charset` attribute that specifies the encoding within the first 1024 bytes of the document; for instance, `<meta charset="UTF-8">` could be used to specify the UTF-8 encoding. This replaces the need for `<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">` although that syntax is still allowed.

For the XML syntax, Web developers have to use the rules as set forth in the XML specification to set the character encoding.

2.2 The Doctype

The HTML syntax requires a doctype to be specified to ensure that the browser renders the page in standards mode. The doctype has no other purpose. [\[DOCTYPE\]](#)

The doctype declaration for the HTML syntax is `<!DOCTYPE html>` and is case-insensitive. Dotypes from earlier versions of HTML were longer because the HTML language was SGML-based and therefore required a reference to a DTD. This is no longer the case and the doctype is only needed to enable standards mode for documents written using the HTML syntax. Browsers already do this for `<!DOCTYPE html>`.

To support legacy markup generators that cannot generate the preferred short doctype, the doctype `<!DOCTYPE html SYSTEM "about:legacy-compact">` is allowed in the HTML syntax.

The strict doctypes for HTML 4.0, HTML 4.01, XHTML 1.0 as well as XHTML 1.1 are also allowed (but are discouraged) in the HTML syntax.

In the XML syntax, any doctype declaration may be used, or it may be omitted altogether. Documents with an XML media type are always handled in standards mode.

2.3 MathML and SVG

The HTML syntax allows for MathML and SVG elements to be used inside a document. An `math` or `svg` start tag causes the HTML parser to switch to a special insertion mode which puts elements and attributes in the appropriate namespaces, does case fixups for elements and attributes that have mixed case, and supports the empty-element syntax as in XML. The syntax is still case-insensitive and attributes allow the same syntax as for HTML elements. Namespace declarations may be omitted. CDATA sections are supported in this insertion mode.

Some MathML and SVG elements cause the parser to switch back to "HTML mode", e.g. `mtext` and `foreignObject`, so you can use HTML elements or a new `math` or `svg` element.

For instance, a very simple document using some of the minimal syntax features could look like:

```
<!doctype html>
<title>SVG in text/html</title>
<p>
  A green circle:
  <svg> <circle r="50" cx="50" cy="50" fill="green"/> </svg>
</p>
```

2.4 Miscellaneous

There are a few other changes in the HTML syntax worthy of mentioning:

- The `⟨` and `⟩` named character references now expand to U+27E8 and U+27E9 (mathematical left/right angle bracket) instead of U+2329 and U+232A (left/right-pointing angle bracket), respectively.
- Many new named character references have been added, including all named character references from MathML.
- Void elements (known as "EMPTY" in HTML4) are allowed to have a trailing slash.
- The ampersand (`&`) may be left unescaped in more cases compared to HTML4.
- Attributes have to be separated by at least one whitespace character.
- Attributes with an empty value may be written as just the attribute name omitting the equals sign and the value, even if the attribute is not a boolean attribute. (It is commonly believed that HTML4 allowed the value to be omitted for boolean attributes. Instead, HTML4 allowed using only the attribute *value* and omitting the attribute name, for enumerated attributes, but this was not supported in browsers.)
- Attributes omitting quotes for the value are allowed to use a larger set of characters compared to HTML4.
- The HTML parser does not do any normalization of whitespace in attribute values; for instance, leading and trailing whitespace in the `id` attribute is not ignored (and thus now invalid), and newline characters can be used in the `value` attribute of the `input` element without using character references.

- The `optgroup` end tag is now optional.
- The `colgroup` start tag is now optional and is inferred by the HTML parser.

3 Language

This section is split up in several subsections to more clearly illustrate the various differences from HTML4.

3.1 New Elements

The following elements have been introduced for better structure:

- `section` represents a generic document or application section. It can be [used together](#) with the [h1](#), [h2](#), [h3](#), [h4](#), [h5](#), and [h6](#) elements to indicate the document structure.
- `article` represents an independent piece of content of a document, such as a blog entry or newspaper article.
- `main` can be used as a container for the dominant contents of another element, such as the main content of the page. In W3C HTML5 and W3C HTML 5.1, only one such element is allowed in a document.
- `aside` represents a piece of content that is only slightly related to the rest of the page.
- In WHATWG HTML, `hgroup` represents the header of a section.
- `header` represents a group of introductory or navigational aids.
- `footer` represents a footer for a section and can contain information about the author, copyright information, etc.
- `nav` represents a section of the document intended for navigation.
- `figure` represents a piece of self-contained flow content, typically referenced as a single unit from the main flow of the document.

```
<figure>
  <video src="example.webm" controls></video>
  <figcaption>Example</figcaption>
</figure>
```

`figcaption` can be used as caption (it is optional).

Then there are several other new elements:

- `video` and `audio` for multimedia content. Both provide an API so application Web developers can script their own user interface, but there is also a way to trigger a user interface provided by the user agent. `source` elements are used together with these elements if there are multiple streams available of different types.

- [track](#) provides text tracks for the [video](#) element.
- [embed](#) is used for plugin content.
- [mark](#) represents a run of text in one document marked or highlighted for reference purposes, due to its relevance in another context.
- [progress](#) represents a completion of a task, such as downloading or when performing a series of expensive operations.
- [meter](#) represents a measurement, such as disk usage.
- [time](#) represents a date and/or time.
- WHATWG HTML and W3C HTML5.1 has [data](#), which allows content to be annotated with a machine-readable value.
- [dialog](#) for showing a dialog.
- [ruby](#), [rt](#), and [rp](#) allow for marking up ruby annotations.
- [bdi](#) represents a span of text that is to be isolated from its surroundings for the purposes of bidirectional text formatting.
- [wbr](#) represents a line break opportunity.
- [canvas](#) is used for rendering dynamic bitmap graphics on the fly, such as graphs or games.
- [menuitem](#) represents a command the user can invoke from a popup menu.
- [details](#) represents additional information or controls which the user can obtain on demand. The [summary](#) element provides its summary, legend, or caption.
- [datalist](#) together with the a new [list](#) attribute for [input](#) can be used to make comboboxes:


```



```
- [keygen](#) represents control for key pair generation.
- [output](#) represents some type of output, such as from a calculation done through scripting.

The [input](#) element's [type](#) attribute now has the following new values:

- [tel](#)
- [search](#)

- [url](#)
- [email](#)
- [datetime](#)
- [date](#)
- [month](#)
- [week](#)
- [time](#)
- [datetime-local](#)
- [number](#)
- [range](#)
- [color](#)

The idea of these new types is that the user agent can provide the user interface, such as a calendar date picker or integration with the user's address book, and submit a defined format to the server. It gives the user a better experience as his input is checked before sending it to the server meaning there is less time to wait for feedback.

3.2 New Attributes

Several attributes have been introduced to various elements that were already part of HTML4:

- The [a](#) and [area](#) elements have the new [download](#) attribute in WHATWG HTML and W3C HTML5.1. WHATWG HTML also has the [ping](#) attribute.
- The [area](#) element, for consistency with the [a](#) and [link](#) elements, now also has the [hreflang](#), [type](#) and [rel](#) attributes.
- The [base](#) element can now have a [target](#) attribute as well, mainly for consistency with the [a](#) element. (This is already widely supported.)
- The [meta](#) element has a [charset](#) attribute now as this was already widely supported and provides a nice way to specify the [character encoding](#) for the document.
- In WHATWG HTML and W3C HTML5.1, the [table](#) element now has a [sortable](#) attribute and the [th](#) element has a [sorted](#) attribute, which provide a means to sort table columns.
- A new [autofocus](#) attribute can be specified on the [input](#) (except when the [type](#) attribute is [hidden](#)), [select](#), [textarea](#) and [button](#) elements. It provides a declarative way to focus a form control during page load. Using this feature should enhance the user experience compared to focusing the element with script as the user can turn it off if the user does not like it, for instance.
- A new [placeholder](#) attribute can be specified on the [input](#) and [textarea](#) elements. It represents a hint intended to aid the user with data entry.

```
<input type=email placeholder="a@b.com">
```

- The new [form](#) attribute for [input](#), [output](#), [select](#), [textarea](#), [button](#), [label](#), [object](#) and [fieldset](#) elements allows for controls to be associated with a form. These elements can

now be placed anywhere on a page, not just as descendants of the [form](#) element, and still be associated with a [form](#).

```
<table>
  <tr>
    <th>Key
    <th>Value
    <th>Action
  <tr>
    <td><form id=1><input name=1-key></form>
    <td><input form=1 name=1-value>
    <td><button form=1 name=1-action value=save> </button>
        <button form=1 name=1-action value=delete> </button>
  ...
</table>
```

- The new [required](#) attribute applies to [input](#) (except when the [type](#) attribute is [hidden](#), [image](#) or some button type such as [submit](#)), [select](#) and [textarea](#). It indicates that the user has to fill in a value in order to submit the form. For [select](#), the first [option](#) element has to be a placeholder with an empty value.

```
<label>Color: <select name=color required>
  <option value="">Choose one
  <option>Red
  <option>Green
  <option>Blue
</select></label>
```

- The [fieldset](#) element now allows the [disabled](#) attribute which disables all descendant controls (excluding those that are descendants of the [legend](#) element) when specified, and the [name](#) attribute which can be used for script access.
- The [input](#) element has several new attributes to specify constraints: [autocomplete](#), [min](#), [max](#), [multiple](#), [pattern](#) and [step](#). As mentioned before it also has a new [list](#) attribute which can be used together with the [datalist](#) element. It also now has the [width](#) and [height](#) attributes to specify the dimensions of the image when using [type=image](#).
- The [input](#) and [textarea](#) elements have a new attribute named [dirname](#) that causes the directionality of the control as set by the user to be submitted as well.
- The [textarea](#) element also has two new attributes, [maxlength](#) and [wrap](#) which control max input length and submitted line wrapping behavior, respectively.
- The [form](#) element has a [novalidate](#) attribute that can be used to disable form validation submission (i.e. the form can always be submitted).
- The [input](#) and [button](#) elements have [formaction](#), [formenctype](#), [formmethod](#), [formnovalidate](#), and [formtarget](#) as new attributes. If present, they override the [action](#), [enctype](#), [method](#), [novalidate](#), and [target](#) attributes on the [form](#) element.
- In WHATWG HTML and W3C HTML5.1, the [input](#) and [textarea](#) have an [inputmode](#) attribute.

- The [menu](#) element has two new attributes: [type](#) and [label](#). They allow the element to transform into a menu as found in typical user interfaces as well as providing for context menus in conjunction with the global [contextmenu](#) attribute.
- In WHATWG HTML and W3C HTML5.1, the [button](#) element has a new [menu](#) attribute, used together with popup menus.
- The [style](#) element has a new [scoped](#) attribute which can be used to enable scoped style sheets. Style rules within such a [style](#) element only apply to the local tree.
- The [script](#) element has a new attribute called [async](#) that influences script loading and execution.
- The [html](#) element has a new attribute called [manifest](#) that points to an application cache manifest used in conjunction with the API for offline Web applications.
- The [link](#) element has a new attribute called [sizes](#). It can be used in conjunction with the [icon](#) relationship (set through the [rel](#) attribute; can be used for e.g. favicons) to indicate the size of the referenced icon, thus allowing for icons of distinct dimensions.
- The [ol](#) element has a new attribute called [reversed](#). When present, it indicates that the list order is descending.
- The [iframe](#) element has three new attributes called [sandbox](#), [seamless](#), and [srcdoc](#) which allow for sandboxing content, e.g. blog comments.
- The [object](#) element has a new attribute called [typemustmatch](#) which allows safer embedding of external resources.
- The [img](#) element has a new attribute called [crossorigin](#) to use CORS in the fetch and if it is successful, allows the image data to be read with the [canvas](#) API. In WHATWG HTML and W3C HTML5.1, the [script](#) element has a [crossorigin](#) attribute to allow script [errors to be reported](#) to [onerror](#) with information about the error. WHATWG HTML and W3C HTML5.1 also has the [crossorigin](#) attribute on the [link](#) element.
- In WHATWG HTML, the [img](#) element has a new attribute called [srcset](#) to support multiple images for different resolutions and different images for different viewport sizes.

Several attributes from HTML4 now apply to all elements. These are called global attributes: [accesskey](#), [class](#), [dir](#), [id](#), [lang](#), [style](#), [tabindex](#) and [title](#). Additionally, XHTML 1.0 only allowed [xml:space](#) on some elements, which is now allowed on all elements in XHTML documents.

There are also several new global attributes:

- The [contenteditable](#) attribute indicates that the element is an editable area. The user can change the contents of the element and manipulate the markup.
- The [contextmenu](#) attribute can be used to point to a context menu provided by the

Web developer.

- The [data-*](#) collection of Web developer-defined attributes. Web developers can define any attribute they want as long as they prefix it with [data-](#) to avoid clashes with future versions of HTML. These are intended to be used to store custom data to be consumed by the Web page or application itself. They are *not* intended for data to be consumed by other parties (e.g. user agents).
- The [draggable](#) and [dropzone](#) attributes can be used together with the new drag & drop API.
- The [hidden](#) attribute indicates that an element is not yet, or is no longer, relevant.
- WHATWG HTML and W3C HTML5.1 has the [inert](#) attribute, intended to make [dialog](#) elements modal.
- The [role](#) and [aria-*](#) collection attributes which can be used to instruct assistive technology. These attributes have slightly different requirements in WHATWG HTML and W3C HTML5/W3C HTML5.1.
- The [spellcheck](#) attribute allows for hinting whether content can be checked for spelling or not.
- The [translate](#) attribute gives a hint to translators whether the content should be translated.

HTML also makes all event handler attributes from HTML4, which take the form [onevent](#), global attributes and adds several new event handler attributes for new events it defines; for instance, the [onplay](#) event handler attribute for the [play](#) event which is used by the API for the media elements ([video](#) and [audio](#)).

3.3 Changed Elements

These elements have slightly modified meanings in HTML to better reflect how they are used on the Web or to make them more useful:

- The [address](#) element is now scoped by the nearest ancestor [article](#) or [body](#) element.
- The [b](#) element now represents a span of text to which attention is being drawn for utilitarian purposes without conveying any extra importance and with no implication of an alternate voice or mood, such as key words in a document abstract, product names in a review, actionable words in interactive text-driven software, or an article lede.
- The [cite](#) element now solely represents the title of a work (e.g. a book, a paper, an essay, a poem, a score, a song, a script, a film, a TV show, a game, a sculpture, a painting, a theatre production, a play, an opera, a musical, an exhibition, a legal case report, etc). Specifically the example in HTML4 where it is used to mark up the name of a person is no longer considered conforming.
- The [dl](#) element now represents an association list of name-value groups, and is

no longer said to be appropriate for dialogue.

- The [hr](#) element now represents a paragraph-level thematic break.
- The [i](#) element now represents a span of text in an alternate voice or mood, or otherwise offset from the normal prose in a manner indicating a different quality of text, such as a taxonomic designation, a technical term, an idiomatic phrase from another language, a thought, or a ship name in Western texts.
- For the [label](#) element the browser should no longer move focus from the label to the control unless such behavior is standard for the underlying platform user interface.
- The [menu](#) element is redefined to be useful for toolbars and popup menus.
- The [noscript](#) element is no longer said to be rendered when the user agent doesn't support a scripting language invoked by a [script](#) element earlier in the document.
- The [s](#) element now represents contents that are no longer accurate or no longer relevant.
- The [script](#) element can now be used for scripts or for custom data blocks.
- The [small](#) element now represents side comments such as small print.
- The [strong](#) element now represents importance rather than strong emphasis.
- The [u](#) element now represents a span of text with an unarticulated, though explicitly rendered, non-textual annotation, such as labeling the text as being a proper name in Chinese text (a Chinese proper name mark), or labeling the text as being misspelt.

3.4 Changed Attributes

Several attributes have changed in various ways.

- The [accept](#) attribute on [input](#) now allows the values [audio/*](#), [video/*](#) and [image/*](#).
- The [accesskey](#) global attribute now allows multiple characters to be specified, which the user agent can choose from.
- The [action](#) attribute on [form](#) is no longer allowed to have an empty URL.
- In WHATWG HTML, the [method](#) attribute has a new keyword [dialog](#), intended to close a [dialog](#) element.
- The [border](#) attribute on [table](#) only allows the values "1" and the empty string. In WHATWG HTML, the [border](#) attribute is obsolete.
- The [colspan](#) attribute on [td](#) and [th](#) now has to be greater than zero.
- The [coords](#) attribute on [area](#) no longer allows a percentage value of the radius

when the element is in the circle state.

- The [data](#) attribute on [object](#) is no longer said to be relative to the [codebase](#) attribute.
- The [defer](#) attribute on [script](#) now explicitly makes the script execute when the page has finished parsing.
- The [dir](#) global attribute now allows the value [auto](#).
- The [enctype](#) attribute on [form](#) now supports the value [text/plain](#).
- The [width](#) and [height](#) attributes on [img](#), [iframe](#) and [object](#) are no longer allowed to contain percentages. They are also not allowed to be used to stretch the image to a different aspect ratio than its intrinsic aspect ratio.
- The [href](#) attribute on [link](#) is no longer allowed to have an empty URL.
- The [href](#) attribute on [base](#) is now allowed to contain a relative URL.
- All attributes that take URLs, e.g. [href](#) on the [a](#) element, now support IRIs if the document's encoding is UTF-8 or UTF-16.
- The [http-equiv](#) attribute on [meta](#) is no longer said to be used by HTTP servers to create HTTP headers in the HTTP response. Instead, it is said to be a pragma directive to be used by the user agent.
- The [id](#) global attribute is now allowed to have any value, as long as it is unique, is not the empty string, and does not contain space characters.
- The [lang](#) global attribute takes the empty string in addition to a valid language identifier, just like [xml:lang](#) does in XML.
- The [media](#) attribute on [link](#) now accepts a media query and defaults to "all".
- The event handler attributes (e.g. [onclick](#)) now always use JavaScript as the scripting language.
- The [value](#) attribute of the [li](#) element is no longer deprecated as it is not presentational. The same goes for the [start](#) and [type](#) attributes of the [ol](#) element.
- The [style](#) global attribute now always uses CSS as the styling language.
- The [tabindex](#) global attribute now allows negative values which indicate that the element can receive focus but cannot be tabbed to.
- The [target](#) attribute of the [a](#) and [area](#) elements is no longer deprecated, as it is useful in Web applications, e.g. in conjunction with [iframe](#).
- The [type](#) attribute on [script](#) and [style](#) is no longer required if the scripting language is JavaScript and the styling language is CSS, respectively.
- The [usemap](#) attribute on [img](#) no longer takes a URL, but instead takes a [valid hash-name reference](#) to a [map](#) element.

The following attributes are allowed but Web developers are discouraged from using them and instead strongly encouraged to use an alternative solution:

- The [border](#) attribute on [img](#). It is required to have the value "0" when present. Web developers can use CSS instead.
- The [language](#) attribute on [script](#). It is required to have the value "JavaScript" (case-insensitive) when present and cannot conflict with the [type](#) attribute. Web developers can simply omit it as it has no useful function.
- The [name](#) attribute on [a](#). Web developers can use the [id](#) attribute instead.

3.5 Obsolete Elements

The elements in this section are not to be used by Web developers. User agents will still have to support them and various sections in HTML define how. E.g. the obsolete [isindex](#) element is handled by the parser section.

The following elements are not in HTML because their effect is purely presentational and their function is better handled by CSS:

- [basefont](#)
- [big](#)
- [center](#)
- [font](#)
- [strike](#)
- [tt](#)

The following elements are not in HTML because using them damages usability and accessibility:

- [frame](#)
- [frameset](#)
- [noframes](#)

The following elements are not included because they have not been used often, created confusion, or their function can be handled by other elements:

- [acronym](#) is not included because it has created a lot of confusion. Web developers are to use [abbr](#) for abbreviations.
- [applet](#) has been obsoleted in favor of [object](#).
- [isindex](#) usage can be replaced by usage of form controls.
- [dir](#) has been obsoleted in favor of [ul](#).

Finally the [noscript](#) element is only conforming in the HTML syntax. It is not allowed in the XML syntax. This is because in order to not only hide visually but also prevent the content to run scripts, apply style sheets, have submittable form controls, load resources, and so forth, the HTML parser parses the content of the [noscript](#) element as

plain text. The same is not possible with an XML parser.

3.6 Obsolete Attributes

Some attributes from HTML4 are no longer allowed in HTML. The specification defines how user agents should process them in legacy documents, but Web developers are not allowed use them and they will not validate.

HTML [has advice](#) on what you can use instead.

- [rev](#) and [charset](#) attributes on [link](#) and [a](#).
- [shape](#) and [coords](#) attributes on [a](#).
- [longdesc](#) attribute on [img](#) and [iframe](#).
- [target](#) attribute on [link](#).
- [nohref](#) attribute on [area](#).
- [profile](#) attribute on [head](#).
- [version](#) attribute on [html](#).
- [name](#) attribute on [img](#) (use [id](#) instead).
- [scheme](#) attribute on [meta](#).
- [archive](#), [classid](#), [codebase](#), [codetype](#), [declare](#) and [standby](#) attributes on [object](#).
- [valuetype](#) and [type](#) attributes on [param](#).
- [axis](#) attribute on [td](#) and [th](#).
- [abbr](#) and [scope](#) attributes on [td](#).
- [summary](#) attribute on [table](#).

In addition, HTML has none of the presentational attributes that were in HTML4 as their functions are better handled by CSS:

- [align](#) attribute on [caption](#), [iframe](#), [img](#), [input](#), [object](#), [legend](#), [table](#), [hr](#), [div](#), [h1](#), [h2](#), [h3](#), [h4](#), [h5](#), [h6](#), [p](#), [col](#), [colgroup](#), [tbody](#), [td](#), [tfoot](#), [th](#), [thead](#) and [tr](#).
- [alink](#), [link](#), [text](#) and [vlink](#) attributes on [body](#).
- [background](#) attribute on [body](#).
- [bgcolor](#) attribute on [table](#), [tr](#), [td](#), [th](#) and [body](#).
- [border](#) attribute on [object](#).
- [cellpadding](#) and [cellspacing](#) attributes on [table](#).

- [char](#) and [charoff](#) attributes on [col](#), [colgroup](#), [tbody](#), [td](#), [tfoot](#), [th](#), [thead](#) and [tr](#).
- [clear](#) attribute on [br](#).
- [compact](#) attribute on [dl](#), [menu](#), [ol](#) and [ul](#).
- [frame](#) attribute on [table](#).
- [frameborder](#) attribute on [iframe](#).
- [height](#) attribute on [td](#) and [th](#).
- [hspace](#) and [vspace](#) attributes on [img](#) and [object](#).
- [marginheight](#) and [marginwidth](#) attributes on [iframe](#).
- [noshade](#) attribute on [hr](#).
- [nowrap](#) attribute on [td](#) and [th](#).
- [rules](#) attribute on [table](#).
- [scrolling](#) attribute on [iframe](#).
- [size](#) attribute on [hr](#).
- [type](#) attribute on [li](#), and [ul](#).
- [valign](#) attribute on [col](#), [colgroup](#), [tbody](#), [td](#), [tfoot](#), [th](#), [thead](#) and [tr](#).
- [width](#) attribute on [hr](#), [table](#), [td](#), [th](#), [col](#), [colgroup](#) and [pre](#).

4 Content Model

The content model is what defines how elements may be nested — what is allowed as children (or descendants) of a certain element.

At a high level, HTML4 had two major categories of elements, "inline" (e.g. [span](#), [img](#), text), and "block-level" (e.g. [div](#), [hr](#), [table](#)). Some elements did not fit in either category.

Some elements allowed "inline" elements (e.g. [p](#)), some allowed "block-level" elements (e.g. [body](#)), some allowed both (e.g. [div](#)), while other elements did not allow either category but only allowed other specific elements (e.g. [dl](#), [table](#)), or did not allow any children at all (e.g. [link](#), [img](#), [hr](#)).

Notice the difference between an element itself being in a certain category, and having a content model of a certain category; for instance, the [p](#) element is itself a "block-level" element, but has a content model of "inline".

To make it more confusing, HTML4 had different content model rules in its Strict, Transitional and Frameset flavors; for instance, in Strict, the [body](#) element allowed only "block-level" elements, but in Transitional, it allowed both "inline" and "block-level".

To make things more confusing still, CSS uses the terms "block-level element" and "inline-level element" for its visual formatting model, which is related to CSS's 'display' property and has nothing to do with HTML's content model rules.

HTML does not use the terms "block-level" or "inline" as part of its content model rules, to reduce confusion with CSS. However, it has more [categories](#) than HTML4, and an element can be part of none of them, one of them, or several of them.

- Metadata content, e.g. [link](#), [script](#).
- Flow content, e.g. [span](#), [div](#), text. This is roughly like HTML4's "block-level" and "inline" together.
- Sectioning content, e.g. [aside](#), [section](#).
- Heading content, e.g. [h1](#).
- Phrasing content, e.g. [span](#), [img](#), text. This is roughly like HTML4's "inline". Elements that are phrasing content are also flow content.
- Embedded content, e.g. [img](#), [iframe](#), [svg](#).
- Interactive content, e.g. [a](#), [button](#), [label](#). Interactive content is not allowed to be nested.

As a broad change from HTML4, HTML no longer has any element that only accepts what HTML4 called "block-level" elements; e.g. the [body](#) element now allows flow content. Thus, This is closer to HTML4 Transitional than HTML4 Strict.

Further changes include:

- The [address](#) element now allows flow content, but with no heading content descendants, no sectioning content descendants, and no [header](#), [footer](#), or [address](#) element descendants.
- HTML4 allowed [object](#) in [head](#). HTML does not.
- WHATWG HTML allows [link](#) and [meta](#) as descendants of [body](#) if they use microdata attributes.
- The [noscript](#) element was a "block-level" element in HTML4, but is phrasing content in HTML.
- The [table](#), [thead](#), [tbody](#), [tfoot](#), [tr](#), [ol](#), [ul](#) and [dl](#) elements are allowed to be empty in HTML.
- Table elements have to conform to the [table model](#) (e.g. two cells are not allowed to overlap).
- The [table](#) element now does not allow [col](#) elements as direct children. However, the HTML parser implies a [colgroup](#) element, so this change should not affect [text/html](#) content.

- The [table](#) element now allows the [tfoot](#) element to be the last child.
- The [caption](#) element now allows flow content, but with no descendant [table](#) elements.
- The [th](#) element now allows flow content, but with no [header](#), [footer](#), sectioning content, or heading content descendants.
- The [a](#) element now has a [transparent](#) content model (except it does not allow interactive content descendants), meaning that it has the same content model as its parent. This means that the [a](#) element can now contain e.g. [div](#) elements, if its parent allows flow content.
- The [ins](#) and [del](#) elements also have a transparent content model. HTML4 had similar rules in prose that could not be expressed in the DTD.
- The [object](#) element also has a transparent content model, after its [param](#) children.
- The [map](#) element also has a transparent content model. The [area](#) element is considered phrasing content if there is a [map](#) element ancestor, which means that they do not need to be direct children of [map](#).
- The [fieldset](#) element no longer requires a [legend](#) child.

5 APIs

HTML has introduced many new APIs and has extended, changed or obsoleted some existing APIs.

5.1 New APIs

HTML introduces a number of APIs that help in creating Web applications. These can be used together with the new elements introduced for applications:

- Media elements ([video](#) and [audio](#)) have APIs for controlling playback, synchronising multiple media elements, and timed text tracks (e.g. subtitles).
- An API for form constraint validation (e.g. the [setCustomValidity\(\)](#) method).
- An API for [commands](#) that the user can invoke.
- An API that enables offline Web applications, with an [application cache](#).
- An API that allows a Web application to register itself for certain protocols or media types, using [registerProtocolHandler\(\)](#) and [registerContentHandler\(\)](#).
- Editing API in combination with a new global [contenteditable](#) attribute.
- Drag & drop API in combination with a [draggable](#) attribute.
- An API that exposes the components of the document's URL and allows scripts to navigate, redirect and reload (the [Location](#) interface).

- An API that exposes the session history and allows scripts to update the document's URL without actually navigating, so that applications don't need to abuse the fragment component for "Ajax-style" navigation (the [History](#) interface).
- An API for base64 conversion ([atob\(\)](#) and [btoa\(\)](#) methods).
- An API to schedule timer-based callbacks ([setTimeout\(\)](#) and [setInterval\(\)](#)).
- An API to prompt the user ([alert\(\)](#), [confirm\(\)](#), [prompt\(\)](#), [showModalDialog\(\)](#)).
- An API for printing the document ([print\(\)](#)).
- An API for handling search providers ([AddSearchProvider\(\)](#) and [IsSearchProviderInstalled\(\)](#)).
- The [Window](#) object has been defined.

WHATWG HTML has further APIs that are not in W3C HTML5 but are separate specifications at the W3C:

- An API for microdata.
- An API for immediate-mode bitmap graphics (the [2d](#) context for the [canvas](#) element).
- An API for cross-document messaging and channel messaging ([postMessage\(\)](#) and [MessageChannel](#)).
- An API for running scripts in the background ([Worker](#) and [SharedWorker](#)).
- An API for client-side storage ([localStorage](#) and [sessionStorage](#)).
- An API for bidirectional client-server communication ([WebSocket](#)).
- An API for server-to-client data push ([EventSource](#)).

5.2 Changed APIs

The following features from DOM Level 2 HTML are changed in various ways:

- [document.title](#) now collapses whitespace on getting.
- [document.domain](#) is made settable, which can change the document's effective script origin.
- [document.open\(\)](#) now either clears the document (if invoked with two or less arguments), or acts like [window.open\(\)](#) (if invoked with three or four arguments). In the former case, throws an exception in XML.
- [document.close\(\)](#), [document.write\(\)](#) and [document.writeln\(\)](#) throw an exception in XML. The latter two now support variadic arguments; they can add text to the document's input stream while it is still being parsed, imply a call to [document.open\(\)](#), or be

ignored altogether in some cases.

- [document.getElementsByName\(\)](#) now returns all HTML elements with a `name` attribute matching the argument.
- `elements` on [HTMLFormElement](#) now returns an [HTMLFormControlsCollection](#) of [button](#), [fieldset](#), [input](#), [keygen](#), [object](#), [output](#), [select](#) and [textarea](#) elements. `length` returns the number of nodes in `elements`.
- `add()` on [HTMLSelectElement](#) now also accepts an integer as its second argument.
- `remove()` on [HTMLSelectElement](#) now removes the first element in the collection if the argument is out of bounds.
- `a` and `area` elements now stringify to their `href` attribute.
- The `click()`, `focus()` and `blur()` methods are now available on all HTML elements.

5.3 Extensions to Document

DOM Level 2 HTML had an [HTMLDocument](#) interface that inherited from [Document](#) and provided HTML-specific members on documents. HTML has moved these members to the [Document](#) interface, and extended it in a number of ways. Since all documents use the [Document](#) interface, the HTML-specific members are now available on all documents, so they are usable in e.g. SVG documents as well. It also has several new members:

- [location](#), [lastModified](#) and [readyState](#) to help resource metadata management.
- [dir](#), [head](#), [embeds](#), [plugins](#), [scripts](#), [commands](#), and a generic name getter, to access various parts of the DOM tree.
- WHATWG HTML has [getItems\(\)](#) for microdata.
- WHATWG HTML and W3C HTML5.1 have [cssElementMap](#) to accompany the [CSS element\(\)](#) feature.
- WHATWG HTML and W3C HTML5.1 have [currentScript](#) which returns the currently running [script](#) element (or null).
- [activeElement](#) and [hasFocus](#) to determine which element is currently focused and whether the [Document](#) has focus respectively.
- [designMode](#), [execCommand\(\)](#), [queryCommandEnabled\(\)](#), [queryCommandIndeterm\(\)](#), [queryCommandState\(\)](#), [queryCommandSupported\(\)](#), [queryCommandValue\(\)](#) for the editing API.
- All event handler IDL attributes. Also, [onreadystatechange](#) is a special event handler IDL attribute that is only available on [Document](#).

Existing scripts that modified the prototype of [HTMLDocument](#) should continue to work because `window.HTMLDocument` now returns the [Document](#) interface object.

5.4 Extensions to `HTMLElement`

The `HTMLElement` interface has also gained several extensions in HTML:

- [translate](#), [hidden](#), [tabIndex](#), [accessKey](#), [draggable](#), [dropzone](#), [contentEditable](#), [contextMenu](#), [spellcheck](#) and [style](#) reflect content attributes.
- [dataset](#) is a convenience feature for handling the `data-*` attributes, which are exposed as camel-cased properties; for instance, `elm.dataset.fooBar = 'test'` sets the `data-foo-bar` content attribute on `elm`.
- WHATWG HTML has [itemScope](#), [itemType](#), [itemId](#), [itemRef](#), [itemProp](#), [properties](#) and [itemValue](#) for microdata.
- [click\(\)](#), [focus\(\)](#) and [blur\(\)](#) allow scripts to simulate clicks and moving focus.
- [accessKeyLabel](#) gives the shortcut key that the user agent has assigned for the element, which the Web developer can influence with the [accesskey](#) attribute.
- [isContentEditable](#) returns true if the element is editable.
- [forceSpellCheck\(\)](#) causes the user agent to check spelling of an element.
- [commandType](#), [commandLabel](#), [commandIcon](#), [commandHidden](#), [commandDisabled](#) and [commandChecked](#) is part of the command API.
- All event handler IDL attributes.

Some members were previously defined on `HTMLElement` but been moved to the `Element` interface in the DOM standard: [\[DOM\]](#)

- [id](#) reflects the `id` content attribute.
- [className](#) reflects the `class` content attribute.
- [classList](#) is a convenient accessor for [className](#). The object it returns exposes methods ([contains\(\)](#), [add\(\)](#), [remove\(\)](#), and [toggle\(\)](#)) for manipulating the element's classes.
- [getElementsByClassName\(\)](#) returns a list of elements with the specified classes.

5.5 Extensions to Other Interfaces

Some interfaces in DOM Level 2 HTML have been extended.

- [HTMLOptionsCollection](#) now has a legacy caller, setter creator, and the members [add\(\)](#), [remove\(\)](#) and [selectedIndex](#)
- [HTMLLinkElement](#) and [HTMLStyleElement](#) now implement the [LinkStyle](#) interface from CSSOM. [\[CSSOM\]](#)
- [HTMLFormElement](#) now has a named getter and an indexed getter.

- [HTMLSelectElement](#) now has a getter, [item\(\)](#) and [namedItem\(\)](#) methods, a setter creator, [selectedOptions](#) and [labels](#) IDL attributes, and members for the form constraint validation API: [willValidate](#), [validity](#), [validationMessage](#), [checkValidity\(\)](#) and [setCustomValidity\(\)](#).
- [HTMLOptionElement](#) now has a constructor [Option](#).
- [HTMLInputElement](#) now has the members [files](#), [height](#), [indeterminate](#), [list](#), [valueAsDate](#), [valueAsNumber](#), [width](#), [stepUp\(\)](#), [stepDown\(\)](#), the form constraint validation API members, [labels](#), and members for the text field selection API: [selectionStart](#), [selectionEnd](#), [selectionDirection](#), [setSelectionRange\(\)](#) and [setRangeText\(\)](#).
- [HTMLTextAreaElement](#) now has the members [textLength](#), the form constraint validation API members, [labels](#) and the text field selection API members.
- [HTMLButtonElement](#) now has the form constraint validation API members and [labels](#).
- [HTMLLabelElement](#) now has the member [control](#).
- [HTMLFieldSetElement](#) now has the members [type](#), [elements](#) and the form constraint validation API members.
- [HTMLAnchorElement](#) now has the members [relList](#), [text](#), and implements the [URLUtils](#) interface which has the members [href](#), [origin](#), [protocol](#), [username](#), [password](#), [host](#), [hostname](#), [port](#), [pathname](#), [search](#), [query](#) and [hash](#). [HTMLLinkElement](#) and [HTMLAreaElement](#) also have the [relList](#) IDL attribute. [HTMLAreaElement](#) also implements the [URLUtils](#) interface.
- [HTMLImageElement](#) now has a constructor [Image](#), and the members [naturalWidth](#), [naturalHeight](#) and [complete](#).
- [HTMLObjectElement](#) now has the members [contentWindow](#), the form constraint validation API members and a legacy caller.
- [HTMLMapElement](#) now has the member [images](#).
- [HTMLTableElement](#) now has the members [createTBody\(\)](#) and, in WHATWG HTML and W3C HTML5.1, [stopSorting\(\)](#).
- In WHATWG HTML and W3C HTML5.1, [HTMLTableHeaderCellElement](#) now has the member [sort\(\)](#).
- [HTMLIFrameElement](#) now has the member [contentWindow](#).

In addition, most new content attributes also have corresponding IDL attributes on the elements' interfaces, e.g. the [sizes](#) IDL attribute on [HTMLLinkElement](#) which reflects the [sizes](#) content attribute.

5.6 Obsolete APIs

Some APIs are now either removed altogether, or marked as obsolete.

All IDL attributes that reflect a content attribute that is itself obsolete, are now also obsolete; for instance, the [bgColor](#) IDL attribute on [HTMLBodyElement](#) which reflects the obsolete [bgcolor](#) content attribute is now obsolete.

The following interfaces are marked obsolete since the elements are obsolete: [HTMLAppletElement](#), [HTMLFrameSetElement](#), [HTMLFrameElement](#), [HTMLDirectoryElement](#) and [HTMLFontElement](#).

The [HTMLIsIndexElement](#) interface is removed altogether since the HTML parser expands an [isindex](#) tag into other elements. The [HTMLBaseFontElement](#) interface is also removed since the element has no effect.

The following members of the [HTMLDocument](#) interface (which have now moved to [Document](#)) are now obsolete: [anchors](#) and [applets](#).

6 HTML Changelogs

The changelogs in this section indicate what has been changed in WHATWG HTML, W3C HTML5 and W3C HTML5.1 between somewhat arbitrary dates, often close to publications of the W3C HTML5 or W3C HTML5.1 drafts. Rationale for changes can be found in the public-html@w3.org and whatwg@whatwg.org mailing list archives, and the [WHATWG Weekly](#) series of blog posts. More fundamental rationale is being collected on the WHATWG [Rationale](#) wiki page. Many editorial and minor technical changes are not included in these changelogs. Implementors are strongly encouraged to follow the development of the main specification on a frequent basis so they become aware of all changes that affect them early on.

The changes in the changelogs are in rough reverse chronological order.

6.1 Changes from 14 September 2012 to 6 May 2013

- The canvas 2d context has a new method [isPointInStroke\(\)](#). (WHATWG HTML and W3C HTML5.1.)
- The [DataTransferItemList](#) interface (part of drag and drop API) now has a [remove\(\)](#) method instead of a deleter. (WHATWG HTML and W3C HTML5.1.)
- The [registerProtocolHandler\(\)](#) API now supports [bitcoin:](#) and [geo:](#) schemes. ([bitcoin:](#) is WHATWG HTML only.)
- The [alert\(\)](#), [confirm\(\)](#) and [prompt\(\)](#) methods now have all arguments optional. (WHATWG HTML and W3C HTML5.1.)
- The [fieldset](#) element can now match the [:invalid](#) pseudo-class. (WHATWG HTML and W3C HTML5.1.)
- The [HTMLBaseFontElement](#) interface has been removed. (WHATWG HTML and W3C HTML5.1.)
- The specification has integrated with the URL standard which effectively added the [origin](#), [username](#), [password](#) and [query](#) IDL attributes to the [a](#) and [area](#) elements and

the `location` object. (WHATWG HTML and W3C HTML5.1.)

- The `hgroup` element has been dropped. (W3C HTML5 and W3C HTML5.1.)
- The HTML parser now better supports `innerHTML` on non-HTML elements. (WHATWG HTML and W3C HTML5.1.)
- Various things that were present in WHATWG HTML but missing in W3C HTML5.1 were "un-forked": The `download` attribute on `a` and `area`, the application cache prefer-online feature, the text range API on `input` and `textarea`, the `cssElementMap` IDL attribute on `Document`, various bits for microdata. (W3C HTML5.1 only.)
- The drag and drop API now has a `dragexit` event. (WHATWG HTML and W3C HTML5.1.)
- The `form` element now receives an `invalid` event when submission fails due to form validation (in addition to the individual controls). (WHATWG HTML and W3C HTML5.1.)
- The `navigator` object now has a `product` IDL attribute that always returns "Gecko" (for compatibility). (WHATWG HTML and W3C HTML5.1.)
- The `time` element's `datetime` IDL attribute got renamed to `dateTime`. (WHATWG HTML and W3C HTML5.1.)
- The `pushState()` and `replaceState()` methods can now be invoked with `null` as the third argument.
- A new `main` element has been added.
- The `stepUp()` and `stepDown()` methods on the `input` element have been tweaked. (WHATWG HTML and W3C HTML5.1.)
- The `img` element now supports progress events. (WHATWG HTML and W3C HTML5.1.)
- A new `fillRule` IDL attribute has been added to the canvas 2d context. (WHATWG HTML only.)
- The `style` IDL attribute on HTML elements is now settable. (WHATWG HTML and W3C HTML5.1.)
- The `media` attribute has been dropped from the `a` and `area` elements. (WHATWG HTML and W3C HTML5.1.)
- Heading elements now support automatic sizing in `hgroup` if they follow an `h1` element. (WHATWG HTML only.)
- The `navigator` object now has a `language` IDL attribute. (WHATWG HTML and W3C HTML5.1.)

- The `menu` API has been revamped. The `command` element was dropped. A new `menuitem` element was added. The `menu` element's `type` attribute now uses the value "popup" instead of "context". The `button` element has a new `menu` attribute and the `type` attribute supports a new value "menu". (WHATWG HTML and W3C HTML5.1.)
- The `table` element now supports sorting columns. The `table` element has a new `sortable` attribute and a `stopSorting()` method. The `th` element has a new `sorted` attribute and a `sort()` method. (WHATWG HTML and W3C HTML5.1.)
- The `autocomplete` attribute on form controls now supports the `cc-type` type. (WHATWG HTML and W3C HTML5.1.)
- A new `currentScript` IDL attribute on `document` was added. (WHATWG HTML and W3C HTML5.1.)
- The `link` and `script` elements now support the `crossorigin` attribute. (WHATWG HTML and W3C HTML5.1.)
- The `canvas` element now supports indirect and proxied rendering contexts, to support drawing from a worker. The `CanvasProxy`, `ImageBitmap` interfaces are introduced, the `canvas` element has new `setContext()` and `transferControlToProxy()` methods, and a new `createImageBitmap()` method on `window` was introduced. (WHATWG HTML and W3C HTML5.1.)
- The canvas 2d context has a new `direction` IDL attribute. (WHATWG HTML only.)
- The `screen` object has a new `canvasResolution` IDL attribute. (WHATWG HTML only.)
- A new `PortCollection()` constructor was added to support sending messages to many ports while allowing them to be garbage collected. (WHATWG HTML only.)
- The `getItem()` method on `Storage` can now return null. (WHATWG HTML only.)
- The `sandbox` attribute on `iframe` supports a new value "allow-pointer-lock". (WHATWG HTML and W3C HTML5.1.)
- The HTML parser now invokes mutation observers. (WHATWG HTML and W3C HTML5.1.)
- The `canvas` element has a new `supportsContext()` method. (WHATWG HTML and W3C HTML5.1.)
- The `abbr` attribute on the `th` element is now conforming.
- A new `forceSpellCheck()` method on HTML elements was added. (WHATWG HTML and W3C HTML5.1.)
- The `EventSource` API now reconnects for DNS errors and TCP-level connection failures. (WHATWG HTML only.)
- A new `fastSeek()` method was added to media elements. (WHATWG HTML and

W3C HTML5.1.)

- The `http+aes:` and `https+aes:` schemes were removed due to lack of interest. (WHATWG HTML only.)
- Navigations with `rel=noreferrer` now does not clone the `sessionStorage`.
- The `error` event for `Worker` objects now has a `column` IDL attribute. (WHATWG HTML only.)
- The `autofocus` attribute on form controls in `dialog` elements now has an effect when the `showModal()` method is invoked.

6.2 Changes from 29 March 2012 to 14 September 2012

- The content model for `ruby` was changed with regards to nested `ruby` elements.
- Self-closing SVG `script` tags in the HTML syntax now execute.
- The placeholder section for the `find()` API has been dropped.
- An encoding declaration is now required in the HTML syntax even if only ASCII characters are used.
- Some bug fixes in the Drag and Drop API.
- The `inBandMetadataTrackDispatchType` IDL attribute was added to `TextTrack`.
- The `TextTrackCue()` constructor now has fewer arguments.
- The `accept` attribute now supports file extensions as well as MIME types.
- The `initialTime` IDL attribute on media elements has been dropped.
- The `startOffsetTime` IDL attribute on media elements has been renamed to `startDate`.

Further changes to WHATWG HTML that do not affect W3C HTML5:

- Several changes and bug fixes in the Text Track API.
- `addElement()` was dropped from the Drag and Drop API.
- Media queries are now proxied for `iframe` elements with the `seamless` attribute.
- The `:enabled` and `:disabled` pseudo-classes now apply to `input` elements in the Hidden state.
- The `ssh`, `sip` and `magnet` schemes are now in the `registerProtocolHandler()` whitelist.
- `table` elements now have 'box-sizing:border-box' by default.
- Bug fixes in the "potentially CORS-enabled fetch" algorithm.

- The document outline algorithm now ignores elements with the `hidden` attribute.
- Markup generators that are unable to provide required `alt` text can now use a specific attribute on `img` that makes validators ignore the missing `alt` error.
- Workers and shared workers now support `data:` URLs.
- The `inputmode` attribute has been added to `input` and `textarea`.
- The `autocomplete` attribute has been extended to support prefilling specific things.
- WebSocket supports sending `ArrayBufferView` as well as `ArrayBuffer`.
- The `border` attribute on `table` is non-conforming again.
- The canvas `ImageData` methods now assume 96dpi, and a set of "HD" methods have been introduced.
- The shared worker `connect` event now also exposes the source port in the `source` IDL attribute.
- Lone surrogates are converted to U+FFFD instead of throwing in `WebSocket send()`.
- The `setRangeText()` method has been added to `input` and `textarea`.
- The `srcset` attribute has been added to `img`.
- Application cache now has an `prefer-online` mode.
- Dialogs are now supported with the `dialog` element, the `inert` global attribute and the `dialog` method on `form`.
- The `resetTransform()` method, `currentTransform` IDL attribute, several IDL attributes for font metrics, `resetClip()` method, `imageSmoothingEnabled` IDL attribute, `addHitRegion()` method, `removeHitRegion()` method, support for dashed lines, have been added to the canvas 2d context.

6.3 Changes from 25 May 2011 to 29 March 2012

- Support for mutation observers was added.
- The `TextTrackCue` members `alignment`, `linePosition`, `textPosition` and `direction` were renamed to `align`, `line`, `position` and `vertical`, respectively.
- The `command` element now has a `command` attribute.
- Drag and drop content is now suggested to be filtered by user agents to prevent XSS attacks.
- The `translate` global attribute was added.
- The `showModalDialog()`, `alert()`, `confirm()` and `prompt()` methods are now allowed to do

nothing during `pagehide`, `beforeunload` and `unload` events.

- The `script` element now supports `before-script-execute` and `after-script-execute` events.
- `window.onerror` now supports a fourth argument for column position.
- The `window.opener` IDL attribute can now return null in some cases.
- The `clearTimeout()` and `clearInterval()` methods were made synonymous.
- The CSS `@global` at-rule was introduced, for use together with `style` elements with the `scoped` attribute.
- The `embed` and `object` elements now have a legacy caller.
- The handling of `window.onerror`'s return value was changed to match reality.
- The `setTimeout()` API is now allowed to be throttled in background tabs.
- The `:valid` and `:invalid` pseudo-classes now apply to `form` elements.
- The `toBlob()` method on `canvas` now honors the origin-clean flag.
- The `activeElement` IDL attribute now points to the relevant browsing context container (e.g. `iframe`) when a child document has focus.
- The `atob()` method now ignores whitespace.
- The `dropzone` attribute was changed to use `"string:"` and `"file:"` instead of `"s:"` and `"f:"`.
- The HTML parser was fixed to correctly handle a case involving foreign lands and foster parenting.
- The date-and-time microsyntaxes now allows a single space instead of a "T".
- Application cache no longer checks the MIME type of the cache manifest.
- The `cueAsSource` IDL attribute on `TextTrackCue` got renamed to `text`.
- The `window.onerror` API is now invoked with dummy arguments for cross-origin scripts.
- The `textarea` element's `value` and `textLength` IDL attributes have their newlines normalized to LF.
- The `q` element now has language-specific quotes rendered by default.
- The `data` element was introduced.
- The `time` element was redesigned to make it match how people wanted to use it. Its `pubdate` attribute was dropped.
- The legacy caller on `form` was removed.

- The `location.resolveURL()` method was removed.
- The `track` element now sniffs instead of obeying the MIME type.
- The `load()` method on documents created by `createDocument()` is now defined on the `XMLDocument` interface.
- Members of `HTMLDocument` moved to `Document` and `window.HTMLDocument` now just returns `window.Document`.
- The `MutableTextTrack` and `TextTrack` interfaces were merged and `TextTrackCue` was made more mutable.
- The `selectedOption` IDL attribute on `input` was dropped.
- Attribute values in Selectors are now case sensitive for all attributes.
- The `readyState` IDL attribute moved from `TextTrack` to `HTMLTrackElement`.
- The `text/html-sandboxed` MIME type was dropped.
- Floating point numbers are now allowed to begin with a "." character.
- Navigating to an audio or video resource is now supported.
- Table cells now allow flow content but does not allow `header`, `footer`, sectioning content or heading content descendants.
- Adding a track to a media element now fires an `addtrack` event on the relevant track list objects.
- Setting `currentTime` on media elements before the media has loaded now defers the seek instead of throwing.
- Plugins are no longer disabled in sandboxed `iframes` if they honor the `sandbox` attribute.
- Some tweaks to history navigation and related events.
- Media elements and `MediaControllers` now get paused when they end.
- Events now support constructors and some `init*Event()` methods were removed.
- Media elements now fire a `suspend` event when the resource is loaded.
- Form submission now normalizes newlines to CRLF.
- Some tweaks around bidi and the `br` element.
- Large parts of the Editing section moved to HTML Editing APIs.
- `UndoManager` and related features moved to `UndoManager` and `DOM Transaction`.
- `isProtocolHandlerRegistered()`, `isContentHandlerRegistered()`, `unregisterProtocolHandler()` and

`unregisterContentHandler()` were added.

- `registerContentHandler()` now has a blacklist of MIME types.
- `registerProtocolHandler()` now has a whitelist of protocols, but also supports any protocol that starts with "`web+`".
- Fragment identifiers for `text/html` resources now don't need to point to an element with a matching ID.
- `audio` elements are now allowed to have zero `source` children.
- There are now some restrictions on the use of bidi formatting characters.
- The `maxlength` and `size` attributes are allowed (but give warnings in validators) on `input` elements with `type=number`.
- The link relation "`shortcut icon`" is now allowed.
- Heading elements are now allowed to have the `heading` and `tab` roles.
- Things that use `EventTarget` now inherit from it instead of using "implements".
- The `setInterval()` API now clamps to 4ms instead of 10ms.
- The `select` element and its `options` collection now have a setter.
- `rel=help` on links now show a help cursor by default.
- Calls to `window.print()` before the document is loaded defers the print until it is loaded.
- Application cache gained an `abort()` method.
- `HTMLCollection`, `DOMTokenList`, `getElementsByClassName()`, `createHTMLDocument()`, HTML-specific overrides to some DOM Core features (like `createElement()`), some definitions, the `id` IDL attribute and ID handling moved to DOM4.
- Fragment identifiers can now survive redirects.
- The `pushState()` and `replaceState()` methods now change the history entry to GET.
- The command API now has its properties prefixed so they are now `commandLabel`, `commandIcon`, `commandHidden`, `commandDisabled` and `commandChecked`.
- The structured clone algorithm now supports sparse arrays.
- `window.postMessage` now supports transferring some objects instead of cloning them, and supports transferring `ArrayBuffer`.
- Application cache was made stricter in its MIME type checking.
- The `placeholder` attribute is now allowed on `input` elements with `type=number`.

- `MediaController` gained an `onended` event listener.
- The HTML parser changed its handling of U+0000 characters in some places.
- The `object` element gained a new attribute `typemustmatch`, to make it safer for Web developers to embed untrusted resources where they expect a certain content type.
- The `form` attribute was removed from `meter` and `progress`.
- The HTML parser was made more forward compatible in its handling of `ruby`.
- Some MIME types (e.g. `text/plain`) that are guaranteed to never be supported as scripting types for `script` were specified, so Web developers can safely use them for custom data blocks.
- `about:blank` documents created from `window.open()` now get a `load` event.
- `window.status` was specified to exist but do nothing.
- Drag and drop `DataTransferItems` was renamed to `DataTransferItemList`.
- Application cache now supports 'no-store' and HTTPS.
- The structured clone algorithm now supports getters.
- The `crossorigin` attribute has been added to `img`, `video` and `audio` to use CORS.
- The `external` IDL attribute has been added on `window` and has the members `AddSearchProvider()` and `IsSearchProviderInstalled()`.

Further changes to WHATWG HTML that do not affect W3C HTML5:

- The 2d context now supports ellipses with the `arc()` and `arcTo()` methods and the new `ellipse()` method.
- The 2d context now supports `Path` objects. SVG path data can be added to a `Path`.
- The `http+aes:` and `https+aes:` URL schemes were added to allow sensitive resources to be held on untrusted servers.
- When the `itemprop` attribute is used on an element where microdata gets its value from an attribute (like `href` on `a` elements), that attribute is now required.
- `PeerConnection` was moved to WebRTC.
- `WebVTT` was moved to its own specification.
- `WebSockets` no longer receive messages in the `CLOSING` state.
- The Atom conversion algorithm was dropped.
- The `itemtype` attribute now allows multiple types.

- `CanvasPixelArray` was dropped in favor of `Uint8ClampedArray`.
- The microdata to RDF conversion algorithm was dropped.
- The `link` element is no longer allowed to have both `rel` and `itemprop`.
- WebSocket API disallows opening an insecure connection if the document uses a secure connection.
- The "storage mutex" is made optional.
- Web Storage no longer supports structured data.
- The `a` element got a new `download` attribute. This attribute is not included in W3C HTML5.
- An experimental specification for the `window.find()` method was added.
- The 2d context `fillText()` and `strokeText()` methods now do not collapse whitespace.
- Microdata now handles infinite loops.
- Web Worker `location` now stringifies.
- Script errors in a Web Worker can now be detected in a parent worker or the document with the `onerror` handler.
- `EventSource` now supports CORS.
- `EventSource` was made stricter in its MIME type checking.
- Web Workers gained the `atob()` and `btoa()` methods.
- Web Workers gained the `ononline` and `onoffline` event handlers.
- WebSockets API has the `error` event again.
- WebSockets API now exposes the selected extensions.
- Various tweaks to the UDP `PeerConnection` API.
- WebSocket close code and reason are now supported in the API.
- Binary data is now supported in WebSockets.
- Redirects in WebSockets are now blocked for security reasons.

6.4 Changes from 5 April 2011 to 25 May 2011

- Support for the `javascript:` scheme in `img`, `object`, CSS, etc, has been dropped.
- The `toBlob()` method has been added to `canvas`.
- The `drawFocusRing()` method on the `canvas` 2d context has been split into two

methods, `drawSystemFocusRing()` and `drawCustomFocusRing()`.

- The `values` attribute on `PropertyNodeList` has been replaced with a `getValues()` method.
- The `select` event has been specified.
- The `selectDirection` IDL attribute has been added to `input` and `textarea`.
- The `:enabled` and `:disabled` pseudo-classes now match `fieldset`, and the `:indeterminate` pseudo-class can now match `progress`.
- The `getKind()` method has been added to `TrackList`.
- The `MediaController` API and the `mediagroup` attribute have been added to synchronize playback of media elements.
- Some ARIA defaults have changed, and it is now invalid to specify ARIA attributes that match the defaults.
- The `getName()` method on `TrackList` was renamed to `getLabel()`.
- The `border` attribute on `table` is now conforming.
- The `u` element is now conforming.
- The `summary` attribute on `table` is now non-conforming.
- The `audio` attribute on `video` was changed to a boolean `muted` attribute.
- The `Content-Language` meta pragma is now non-conforming.

6.5 Changes from 13 January 2011 to 5 April 2011

- The `pushState` and `replaceState` features have been changed based on implementation feedback in Firefox, and `history.state` has been introduced.
- The `tracks` IDL attribute on media elements has been renamed to `textTracks`.
- Event handler content attributes now support JavaScript strict mode.
- The `forminput` and `formchange` events, and the `dispatchFormInput()` and `dispatchFormChange()` methods have been dropped.
- The `rel` keywords `archives`, `up`, `last`, `index`, `first` and related synonyms have been dropped.
- Removing a media element from the DOM and inserting it again in the same script now doesn't pause the media element.
- The `video` element's letterboxing rules are now specified in terms of CSS 'object-fit'.
- Cross-origin fonts now don't leak information about the font when drawn on a

`canvas`.

- The character encoding declaration is now allowed to be within the first 1024 bytes instead of the first 512 bytes.
- The `onerror` event handler on `window` is now invoked for compile-time script errors as well as runtime errors.
- Script-inserted `script` elements now have `async` default to `true`, which can be set to `false` to make the scripts execute in insertion order.
- The `atob()` and `btoa()` methods have been specified.
- The suggested file extension for application cache manifest files has been changed from `.manifest` to `.appcache`.
- The `action` and `formaction` attributes are no longer allowed to have the empty string as value.

6.6 Changes from 19 October 2010 to 13 January 2011

- Drag and drop model was refined.
- A new global `dropzone` attribute was added.
- A new `bdi` element was added to aid with user-generated content that may have bidi implications.
- The `dir` attribute gained a new `"auto"` value.
- A `dirname` attribute was added to `input` elements. When specified the directionality as specified by the user will be submitted to the server as well.
- A new `track` element and associated TextTrack API were added for video text tracks.
- The `type` attribute on the `ol` element is now allowed.

The `getSelection()` API moved to a separate [DOM Range](#) draft. Similarly `UndoManager` has been removed from the W3C copy of HTML5 for now as it is not ready yet.

6.7 Changes from 24 June 2010 to 19 October 2010

- Numerous changes to the HTML parsing algorithm based on implementation feedback.
- The `hidden` attribute now works for table-related elements.
- The `canvas` `getContext()` method is now defined to be able to handle multiple contexts better.
- The media elements' `startTime` IDL attribute was renamed to `initialTime` and

`startOffsetTime` was added.

- The `prefetch` link relationship can now be used on `a` elements.
- The `datetime` attribute of `ins` and `del` no longer requires a time to be specified.
- Using PUT and DELETE as HTTP methods for the `form` element is no longer supported.
- The `s` element is no longer deprecated.
- The `video` element has a new `audio` attribute.

Per usual, lots of other minor fixes have been made as well.

6.8 Changes from 4 March 2010 to 24 June 2010

- The `ping` attribute has been removed from the W3C version of HTML5.
- The `title` element is optional for `iframe srcdoc` documents and other scenarios where a title is already available. As is the case with email.
- `keywords` is now a standard metadata name for the `meta` element.
- The `allow-top-navigation` value has been added for the `sandbox` attribute on the `iframe` element. It allows the embedded content to navigate its parent when specified.
- The `wbr` element has been added.
- The `alternate` keyword for the `rel` attribute of the `link` element can now be used to point to feeds again, even if the feed is not an alternative for the document.
- The HTML to Atom mapping has been removed from the W3C version of HTML5.

In addition lots of minor changes, clarifications, and fixes have been made to the document.

6.9 Changes from 25 August 2009 to 4 March 2010

- The `dialog` element has been removed. A section with advice on how to mark up conversations has effectively replaced it.
- `document.head` has been introduced to provide convenient access to the `head` element from script.
- The link type `feed` has been removed. `alternate` with specific media types is to be used instead.
- `createHTMLDocument()` has been introduced as API to allow easy creation of HTML documents.
- Both the `meter` and `progress` elements no longer have "magic" processing of their

contents because it could not be made to work internationally.

- The `meter` and `progress` elements, as well as the `output` element, can now be labeled using the `label` element.
- A new media type, `text/html-sandboxed`, was introduced to allow hosting of potentially hostile content without it causing harm.
- A `srcdoc` attribute for the `iframe` element was introduced to allow embedding of potentially hostile content inline. It is expected to be used together with the `sandbox` and `seamless` attributes.
- The `figure` element now uses a new element `figcaption` rather than `legend` because people want to use HTML long before it reaches W3C Recommendation.
- The `details` element now uses a new element `summary` for exactly the same reason.
- The `autobuffer` attribute on media elements was renamed to `preload`.

A whole lot of other smaller issues have also been resolved. The above list summarizes what is thought to be of primary interest to Web developers.

In addition to all of the above, Microdata, the 2D context API for `canvas`, and Web Messaging (`postMessage()` API) have been split into their own drafts at the W3C (the WHATWG still publishes a version of HTML that includes them):

- [HTML Microdata](#)
- [HTML Canvas 2D Context](#)
- [HTML5 Web Messaging](#)

Specific microdata vocabularies are gone altogether in the W3C draft of HTML5 and are not published as a separate draft. The WHATWG draft of HTML still includes them.

6.10 Changes from 23 April 2009 to 25 August 2009

- When the `time` element is empty user agents have to render the time in a locale-specific manner.
- The `load` event is dispatched at `Window`, but now has `Document` as its target.
- `pushState()` now affects the `Referer` (sic) header.
- `onundo` and `onredo` are now on `Window`.
- Media elements now have a `startTime` member that indicates where the current resource starts.
- `header` has been renamed to `hgroup` and a new `header` element has been introduced.
- `createImageData()` now also takes `ImageData` objects.

- `createPattern()` can now take a `video` element as argument too.
- The `footer` element is no longer allowed in `header` and `header` is not allowed in `address` or `footer`.
- A new control has been introduced: `<input type="tel">`
- The Command API now works for all elements.
- `accesskey` is now properly defined.
- `section` and `article` now take a `cite` attribute.
- A new feature called Microdata has been introduced which allows people to embed custom data structures in their HTML documents.
- Using the Microdata model three predefined vocabularies have also been included: vCard, vEvent, and a model for licensing.
- Drag and drop has been updated to work with the Microdata model.
- The [last of the parsing quirks](#) has been defined.
- `maxLength` has been added as member of the `textarea` element.
- The `rp` element now takes phrasing content rather than a single character.
- `location.reload()` is now defined.
- The `hashchange` event now fires asynchronously.
- Rules for compatibility with XPath 1.0 and XSLT 1.0 have been added.
- The `spellcheck` IDL attribute now maps to a `DOMString`.
- `hasFeature()` support has been reduced to a minimum.
- The `Audio()` constructor sets the `autobuffer` attribute.
- The `td` element is no longer allowed in `thead`.
- The `input` element and `DataTransfer` object now have a `files` IDL attribute.
- The `datagrid` and `bb` have been removed due to their design not being agreed upon.
- The cue range API has been removed from the media elements.
- Support for WAI-ARIA has been integrated.

On top of this list quite a few minor clarifications, typos, issues specific to implementors, and other small problems have been resolved.

In addition, the following parts of HTML have been taken out and will likely be further

developed at the IETF:

- Definition of URLs.
- Definition of Content-Type sniffing.

6.11 Changes from 12 February 2009 to 23 April 2009

- A new global attribute called `spellcheck` has been added.
- Defined that JavaScript `this` in the global object returns a `WindowProxy` object rather than the `Window` object.
- The `value` IDL attribute for `input` elements in the File Upload state is now defined.
- Definition of `designMode` was changed to be more in line with legacy implementations.
- The `drawImage()` method of the 2D drawing API can now take a `video` element as well.
- The way media elements load resources has been changed.
- `document.domain` is now IPv6-compatible.
- The `video` element gained an `autobuffer` boolean attribute that serves as a hint.
- You are now allowed to specify the `meta` element with a `charset` attribute in XML documents if the value of that attribute matches the encoding of the document. (Note that it does not specify the value, it is just a talisman.)
- The `bufferingRate` and `bufferingThrottled` members of media elements have been removed.
- The media element resource selection algorithm is now asynchronous.
- The `postMessage()` API now takes an array of `MessagePort` objects rather than just one.
- The second argument of the `add()` method on the `select` element and the `options` member of the `select` element is now optional.
- The `action`, `enctype`, `method`, `novalidate`, and `target` attributes on `input` and `button` elements have been renamed to `formaction`, `formenctype`, `formmethod`, `formnovalidate`, and `formtarget`.
- A "storage mutex" concept has been added to deal with separate pages trying to change a storage object (`document.cookie` and `localStorage`) at the same time. The `Navigator` gained a `getStorageUpdates()` method to allow it to be explicitly released.
- A syntax for SVG similar to MathML is now defined so that SVG can be included in `text/html` resources.

- The `placeholder` attribute has been added to the `textarea` element.
- Added a `keygen` element for key pair generation.
- The `datagrid` element was revised to make the API more asynchronous and allow for unloaded parts of the grid.

In addition, several parts of HTML have been taken out and will be further developed by the Web Applications Working Group as standalone specifications:

- [WebSocket API](#)
- [WebSocket protocol](#)
- [Server-Sent Events](#)
- [Web Storage](#) (`localStorage` and `sessionStorage`)
- [Web SQL Database](#)

6.12 Changes from 10 June 2008 to 12 February 2009

- The `data` member of `ImageData` objects has been changed from an array to a `CanvasPixelArray` object.
- Shadows are now required from implementations of the `canvas` element and its API.
- Security model for `canvas` is clarified.
- Various changes to the processing model of `canvas` have been made in response to implementation and Web developer feedback. E.g. clarifying what happens when NaN and Infinity are passed and fixing the definitions of `arc()` and `arcTo()`.
- `innerHTML` in XML was slightly changed to improve round-tripping.
- The `toDataURL()` method on the `canvas` element now supports setting a quality level when the media type argument is `image/jpeg`.
- The `poster` attribute of the `video` element now affects its intrinsic dimensions.
- The behavior of the `type` attribute of the `link` element has been clarified.
- Sniffing is now allowed for `link` when the expected type is an image.
- A section on URLs is introduced dealing with how URL values are to be interpreted and what exactly Web developers are required to do. Every feature of the specification that uses URLs has been reworded to take the new URL section into account.
- It is now explicit that the `href` attribute of the `base` element does not depend on `xml:base`.

- It is now defined what the behavior should be when the base URL changes.
- URL decomposition IDL attributes are now more aligned with Internet Explorer.
- The `xmlns` attribute with the value `http://www.w3.org/1999/xhtml` is now allowed on all HTML elements.
- `data-*` attributes and custom attributes on the `embed` element now have to match the XML `Name` production and cannot contain a colon.
- WebSocket API is introduced for bidirectional communication with a server.
- The default value of `volume` on media elements is now 1.0 rather than 0.5.
- `event-source` was renamed to `eventsourcing` because no other HTML element uses a hyphen.
- A message channel API has been introduced augmenting `postMessage()`.
- A new element named `bb` has been added. It represents a user agent command that the user can invoke.
- The `addCueRange()` method on media elements has been modified to take an identifier which is exposed in the callbacks.
- It is now defined how to mutate a DOM into an infocet.
- The `parent` attribute of the `Window` object is now defined.
- The `embed` element is defined to do extension sniffing for compatibility with servers that deliver Flash as `text/plain`. (This is marked as an issue in the specification to figure out if there is a better way to make this work.)
- The `embed` can now be used without its `src` attribute.
- `getElementsByClassName()` is defined to be ASCII case-insensitive in quirks mode for consistency with CSS.
- In HTML documents `localName` no longer returns the node name in uppercase.
- `data-*` attributes are defined to be always lowercase.
- The `opener` attribute of the `Window` object is not to be present when the page was opened from a link with `target="_blank"` and `rel="noreferrer"`.
- The `top` attribute of the `Window` object is now defined.
- The `a` element now allows nested flow content, but not nested interactive content.
- It is now defined what the `header` element means to document summaries and table of contents.
- What it means to fetch a resource is now defined.

- Patterns are now required for the `canvas` element.
- The `autosubmit` attribute has been removed from the `menu` element.
- Support for `outerHTML` and `insertAdjacentHTML()` has been added.
- `xml:lang` is now allowed in HTML when `lang` is also specified and they have the same value. In XML `lang` is allowed if `xml:lang` is also specified and they have the same value.
- The `frameElement` attribute of the `Window` object is now defined.
- An event loop and task queue is now defined detailing script execution and events. All features have been updated to be defined in terms of this mechanism.
- If the `alt` attribute is omitted a `title` attribute, an enclosing `figure` element with a `legend` element descendant, or an enclosing section with an associated heading must be present.
- The `irrelevant` attribute has been renamed to `hidden`.
- The `definitionURL` attribute of MathML is now properly supported. Previously it would have ended up being all lowercase during parsing.
- User agents must treat US-ASCII as Windows-1252 for compatibility reasons.
- An alternative syntax for the DOCTYPE is allowed for compatibility with some XML tools.
- Data templates have been removed (consisted of the `datatemplate`, `rule` and `nest` elements).
- The media elements now support just a single `loop` attribute.
- The `load()` method on media elements has been redefined as asynchronous. It also tries out files in turn now rather than just looking at the `type` attribute of the `source` element.
- A new member called `canPlayType()` has been added to the media elements.
- The `totalBytes` and `bufferedBytes` attributes have been removed from the media elements.
- The `Location` object gained a `resolveURL()` method.
- The `q` element has changed again. Punctuation is to be provided by the user agent again.
- Various changes were made to the HTML parser algorithm to be more in line with the behavior Web sites require.
- The `unload` and `beforeunload` events are now defined.

- The IDL blocks in the specification have been revamped to be in line with the upcoming Web IDL specification.
- Table headers can now have headers. User agents are required to support a `headers` attribute pointing to a `td` or `th` element, but Web developers are required to only let them point to `th` elements.
- Interested parties can now register new `http-equiv` values.
- When the `meta` element has a `charset` attribute it must occur within the first 512 bytes.
- The `StorageEvent` object now has a `storageArea` attribute.
- It is now defined how HTML is to be used within the SVG `foreignObject` element.
- The notification API has been dropped.
- How `[[Get]]` works for the `HTMLDocument` and `Window` objects is now defined.
- The `Window` object gained the `locationbar`, `menubar`, `personalbar`, `scrollbars`, `statusbar` and `toolbar` attributes giving information about the user interface.
- The application cache section has been significantly revised and updated.
- `document.domain` now relies on the Public Suffix List. [\[PSL\]](#)
- A non-normative rendering section has been added that describes user agent rendering rules for both obsolete and conforming elements.
- A normative section has been added that defines when certain selectors as defined in the Selectors and the CSS3 Basic User Interface Module match HTML elements. [\[SELECTORS\]](#) [\[CSSUI\]](#)

Web Forms 2.0, previously a standalone specification, has been fully integrated into HTML since last publication. The following changes were made to the forms chapter:

- Support for XML submission has been removed.
- Support for form filling has been removed.
- Support for filling of the `select` and `datalist` elements through the `data` attribute has been removed.
- Support for associating a field with multiple forms has been removed. A field can still be associated with a form it is not nested in through the `form` attribute.
- The `dispatchChangeInput()` and `dispatchFormChange()` methods have been removed from the `select`, `input`, `textarea`, and `button` elements.
- Repetition templates have been removed.
- The `inputmode` attribute has been removed.

- The `input` element in the File Upload state no longer supports the `min` and `max` attributes.
- The `allow` attribute on `input` elements in the File Upload state is no longer authoritative.
- The `pattern` and `accept` attributes for `textarea` have been removed.
- RFC 3106 is no longer explicitly supported.
- The `submit()` method now just submits, it no longer ensures the form controls are valid.
- The `input` element in the Range state now defaults to the middle, rather than the minimum value.
- The `size` attribute on the `input` element is now conforming (rather than deprecated).
- `object` elements now partake in form submission.
- The `type` attribute of the `input` element gained the values `color` and `search`.
- The `input` element gained a `multiple` attribute which allows for either multiple e-mails or multiple files to be uploaded depending on the value of the `type` attribute.
- The `input`, `button` and `form` elements now have a `novalidate` attribute to indicate that the form fields should not be required to have valid values upon submission.
- When the `label` element contains an `input` it may still have a `for` attribute as long as it points to the `input` element it contains.
- The `input` element now has an `indeterminate` IDL attribute.
- The `input` element gained a `placeholder` attribute.

6.13 Changes from 22 January 2008 to 10 June 2008

- Implementation and authoring details around the `ping` attribute have changed.
- `<meta http-equiv=content-type>` is now a conforming way to set the character encoding.
- API for the `canvas` element has been cleaned up. Text support has been added.
- `globalStorage` is now restricted to the same-origin policy and renamed to `localStorage`. Related event dispatching has been clarified.
- `postMessage()` API changed. Only the origin of the message is exposed, no longer the URL. It also requires a second argument that indicates the origin of the target document.
- Drag and drop API has got clarification. The `dataTransfer` object now has a `types`

attribute indicating the type of data being transferred.

- The `m` element is now called `mark`.
- Server-sent events has changed and gotten clarification. It uses a new format so that older implementations are not broken.
- The `figure` element no longer requires a caption.
- The `ol` element has a new `reversed` attribute.
- Character encoding detection has changed in response to feedback.
- Various changes have been made to the HTML parser section in response to implementation feedback.
- Various changes to the editing section have been made, including adding `queryCommandEnabled()` and related methods.
- The `headers` attribute has been added for `td` elements.
- The `table` element has a new `createTBody()` method.
- MathML support has been added to the HTML parser section. (SVG support is still awaiting input from the SVG WG.)
- Web developer-defined attributes have been added. Web developers can add attributes to elements in the form of `data-name` and can access these through the DOM using `dataset[name]` on the element in question.
- The `q` element has changed to require punctuation inside rather than having the browser render it.
- The `target` attribute can now have the value `_blank`.
- The `showModalDialog` API has been added.
- The `document.domain` API has been defined.
- The `source` element now has a new `pixelratio` attribute useful for videos that have some kind encoding error.
- `bufferedBytes`, `totalBytes` and `bufferingThrottled` IDL attributes have been added to the `video` element.
- Media `begin` event has been renamed to `loadstart` for consistency with the Progress Events specification.
- `charset` attribute has been added to `script`.
- The `iframe` element has gained the `sandbox` and `seamless` attributes which provide sandboxing functionality.

- The `ruby`, `rt` and `rp` elements have been added to support ruby annotation.
- A `showNotification()` method has been added to show notification messages to the user.
- Support for `beforeprint` and `afterprint` events has been added.

Acknowledgments

The editors would like to thank Ben Millard, Bruce Lawson, Cameron McCormack, Charles McCathieNevile, Dan Connolly, David Håsäther, Dennis German, Frank Ellermann, Frank Palinkas, Futomi Hatano, Gordon P. Hemsley, Henri Sivonen, James Graham, Jens Meiert, Jeremy Keith, Jukka K. Korpela, Jürgen Jeka, Krijn Hoetmer, Leif Halvard Silli, Maciej Stachowiak, Mallory van Achterberg, Marcos Caceres, Mark Pilgrim, Martijn Wargers, Martin Leese, Martyn Haigh, Masataka Yakura, Michael Smith, Mike Taylor, *Ms2ger*, Olivier Gendrin, Øistein E. Andersen, Philip Jägenstedt, Philip Taylor, Randy Peterman, Steve Faulkner, Toby Inkster, Xaxio Brandish, and Yngve Spjeld Landro for their contributions to this document as well as to all the people who have contributed to HTML over the years for improving the Web!

References

[CSSOM]

[CSS Object Model \(CSSOM\)](#), Glenn Adams and Simon Pieters. W3C.

[CSSUI]

[CSS Basic User Interface Module](#), Tantek Çelik. W3C.

[DOCTYPE]

[Activating Browser Modes with Doctype](#), Henri Sivonen.

[DOM]

[DOM](#), Anne van Kesteren, Aryeh Gregor and Ms2ger. WHATWG.

[DOM2HTML]

[Document Object Model \(DOM\) Level 2 HTML Specification](#), Johnny Stenback, Philippe Le Hégarret and Arnaud Le Hors. W3C.

[HTML]

[HTML](#), Ian Hickson. WHATWG.

[HTML4]

[HTML 4.01 Specification](#), Dave Raggett, Arnaud Le Hors and Ian Jacobs. W3C.

[HTML5]

[HTML5](#), Robin Berjon, Steve Faulkner, Travis Leithead et al.. W3C.

[HTML5NIGHTLY]

[HTML 5.1 Nightly](#), Robin Berjon, Steve Faulkner, Travis Leithead et al.. W3C.

[PSL]

[Public Suffix List](#). Mozilla.

[SELECTORS]

[Selectors Level 4](#), Erika J. Etemad. W3C.

[XHTML1]

[XHTML™ 1.1 - Module-based XHTML - Second Edition](#), Murray Altheim and Shane McCarron.

[XML]

[Extensible Markup Language](#), Tim Bray, Jean Paoli, C. M. Sperberg-McQueen et al.. W3C.

[XMLNS]

[Namespaces in XML](#), Tim Bray, Dave Hollander, Andrew Layman et al.. W3C.